

SPECIFICATIONS

Potter Roemer/ Fire Pro® truck mount monitors are designed with a 1-1/2" NH swivel to be used with a soft hose. The balanced flow single waterway design and precision machining on swivel joints reduces friction loss while improving stream and distance, and ensures ease of operation at all pressure/ flow ranges. Carbon Steel construction with 304 stainless steel swivels. Standard red polyester powder coating inside and out protect against corrosion. Type 304 stainless steel ball bearings in joints ensure easy movement and reliable operation.



FPTM-125

REGULARLY FURNISHED

- 1-1/2" Waterway
- Seamless carbon or stainless steel construction
- Zerk fitting for lubrication
- Low friction loss
- 360° horizontal and 120° vertical travel
- 125-350 GPM (473-1325 lpm)
- "T" Pin for removal of monitor from base when not in use

MODEL	INLET In (mm)	OUTLET In (mm)	WEIGHT Lbs (kg)
FPTM-125	1-1/2" SWIVEL (38)	1-1/2" (38)	27 (12)

PRODUCT OPTIONS

- ☐ Drainage Provisions
- ☐ Gauge and Guard
- ☐ Metric Flanges
- ☐ Parallel Handle
- ☐ Shut Off Valve
- ☐ Steering Wheel Handle

FINISHES:

- ☐ Customer Colors _____ (Specify)

