

### SPECIFICATIONS

Fire Pro® monitors are designed to meet all requirements of municipal and petrochemical applications. The balanced flow single waterway design and precision machining on swivel joints reduces friction loss while improving stream and distance, and ensures ease of operation at all pressure/flow ranges.

Carbon Steel construction with 304 stainless steel swivels. Standard red polyester powder coating inside and out protect against corrosion. Type 304 stainless steel ball bearings in joints ensure easy movement and reliable operation.

### FEATURES

- 3.0" Waterway W/ 2.5" outlet
- Seamless carbon or stainless steel construction
- Zerk fitting for lubrication
- Low friction loss
- 360° horizontal and 120° vertical travel
- 250-1250 GPM (946-4732 lpm)

### OPTIONS

- ☐ Drainage Provisions
- ☐ Gauge and Guard
- ☐ Metric Flanges
- ☐ Parallel Handle
- ☐ Steering Wheel Handle
- ☐ Shut Off Valve



FP3SD-1200 (Shown)

MODEL	INLET In (mm)	OUTLET In (mm)	WEIGHT Lbs (kg)
FP3SD-1200	3.0" FLANGE (76)	2.5 NH (64)	64 (29)
FP3SD(F/M)-1200	3.0" NPT (76)	2.5 NH (64)	61 (28)
FP4SD-1200	4.0" FLANGE (102)	2.5 NH (64)	68 (31)



