

SPECIFICATIONS

Potter Roemer/ Fire Pro® Industrial Station monitors are ideal for withstanding extreme weather, industrial rigors, and petrochemical exposure often found in marine, offshore and industrial environments. Brass construction. Standard red powder coating gives a tough corrosion resistant finish.



REGULARLY FURNISHED

- 3" Waterway
- Brass construction
- 360° horizontal and 120° vertical travel
- 1250 GPM (4732 lpm)

MODEL	INLET In (mm)	OUTLET In (mm)	HEIGHT In (mm)	WIDTH In (mm)	WEIGHT Lbs (kg)
FP10611-3	3" FLANGE (76)	2-1/2" (64)	16" (406)	15" (381)	56 (25)
FP10611-3F	3" NPT (76)	2-1/2" (64)	16" (406)	15" (381)	56 (25)
FP10611-4	4" FLANGE (102)	2-1/2" (64)	16" (406)	15" (381)	56 (25)
FP10612-3	3" FLANGE (76)	2-1/2" (64)	16" (406)	15" (381)	60 (27)
FP10612-3F	3" NPT (76)	2-1/2" (64)	16" (406)	15" (381)	60 (27)
FP10612-4	4" FLANGE (102)	2-1/2" (64)	16" (406)	15" (381)	60 (27)

