

SPECIFICATIONS

Fire Pro® snorkel monitors feature a 120° vertical travel that is ideal for tank cleaning and any other wash down application. The balanced flow single waterway design and precision machining on swivel joints reduces friction loss while improving stream and distance, and ensures ease of operation at all pressure/ flow ranges.

Stainless Steel construction with 304 stainless steel swivels. Standard red polyester powder coating inside and out protect against corrosion. Type 304 stainless steel ball bearings in joints ensure easy movement and reliable operation.

FEATURES

- 3.0" Waterway
- Vertical Blade lock
- All stainless steel construction
- Zerk fitting for lubrication
- Low friction loss
- 360° horizontal and 120° vertical travel
- 350-1250 GPM (1325-4732 lpm)

OPTIONS

- ☐ Drainage Provisions
- ☐ Gauge and Guard
- ☐ Metric Flanges
- ☐ Shut Off Valve



| MODEL | INLET In (mm) | OUTLET In (mm) | WEIGHT Lbs (kg) |
|--------------------|----------------------|-------------------|--------------------|
| FP3SN-1200-BL | 3.0" FLANGE (76) | 2.5 NH (64) | 61 (28) |
| FP3SN(F/M)-1200-BL | 3.0" NPT (76) | 2.5 NH (64) | 54 (25) |
| FP4SN-1200-BL | 4.0" FLANGE (102) | 2.5 NH (64) | 67 (30) |

