

SPECIFICATIONS

Potter Roemer/ Fire Pro® station monitors were specifically designed to meet all requirements of municipal and petrochemical applications. The balanced flow single waterway design and precision machining on swivel joints reduces friction loss while improving stream and distance, and ensures ease of operation at all pressure/ flow ranges. Carbon Steel construction with 304 stainless steel swivels. Standard red polyester powder coating inside and out protect against corrosion. Type 304 stainless steel ball bearings in joints ensure easy movement and reliable operation.



REGULARLY FURNISHED

- 3" Waterway to 2-1/2" Outlet
- Seamless carbon or stainless steel construction
- Zerk fitting for lubrication
- Low friction loss
- 360° horizontal and 120° vertical travel
- 1200 GPM (4542 lpm)

MODEL	INLET In (mm)	OUTLET In (mm)	WEIGHT Lbs (kg)
FP3-1200	3" FLANGE (64)	3" (76) Waterway W/ 2-1/2" (64) Male Thread	52 (24)
FP3(F/M)-1200	3" NPT (64)	3" (76) Waterway W/ 2-1/2" (64) Male Thread	52 (24)
FP4-1200	4" FLANGE (76)	3" (76) Waterway W/ 2-1/2" (64) Male Thread	52 (24)

PRODUCT OPTIONS

- ☐ Drainage Provisions
- ☐ Gauge and Guard
- ☐ Metric Flanges
- ☐ Parallel Handle
- ☐ Shut Off Valve
- ☐ Steering Wheel Handle

FINISHES:

- ☐ Customer Colors _____ (Specify)

