# **SILVENT X01**




#### Stainless steel multi-Laval nozzle

SILVENT X01 is a stainless steel blowing nozzle with patented multi-Laval technology. The energy saving air nozzle is part of Silvent's revolutionary new X-series. The nozzle in the new X series has a completely new and innovative design that creates a concentrated jet of air with reduced turbulence, thus enabling a more targeted, effective blowing force. Thanks to the newly patented technology, the air nozzle's design optimizes the air pressure's change from potential energy to aimed concentrated kinetic energy. This allows for maximal use of the air pressure. The unique design makes it possible to reduce noise levels during blowing by more than 10dB(A). The blowing nozzle is perfect for environments with high cleanliness requirements, such as the food industry. The nozzle has a 1/8" connection.

# **Dimensions**





#### **TECHNICAL DATA**

Replace open pipe Ø (mm)	4		
Blowing force (N)	2.8		
Air consumption (Nm³/h)	14		
Sound level (dB(A))	78		
Nozzle technology	Multi-Laval		
Material (nozzle)	1.4404 (316L)		
Connection	G 1/8"		
Weight (g)	9		
Max temp (°C)	400		
Max op. pressure (MPa)	1.0		

Noise reduction	17 dB(A)	Energy savings	<b>16</b> Nm³/h
-----------------	----------	----------------	-----------------


Feed pressure = 500 (kPa)
Material specification: EN 1.4404

# Blowing properties at different pressures (kPa)

X01	200	400	600	800	1000
Blowing force (N)	1.2	2.3	3.4	4.5	5.6
Air consumption (Nm³/h)	8.0	12.0	16.0	20.0	24.0
Sound level (dB(A))	72.0	76.0	79.0	82.0	84.0

<sup>\*</sup>For further information, see page 166 or visit silvent.com.

## Blowing coverage (mm)



## **ALTERNATIVES**





SILVENT G01: with female connection thread M7x0.75. Dimensions: Ø8.5x21 (Ø0.33x0.83"). Otherwise, the same performance as X01.





SILVENT X01-200 - X01-500: nozzle mounted on a bendable stainless steel FlexBlow hose that keeps the desired position, even when blowing at high pressure. Available in 4 different standard lengths. The FlexBlow hose has a 1/8" male connection thread. Otherwise, the same performance as X01.

## **ACCESSORIES**



# Adjustable Swivel

PSK 18. Material: stainless steel. For more information see page 156.