

Spring Rewind Reels

Hannay Series SSN700

To handle 1/4" through 1/2" I.D. hose

Features

- Narrow frame and compact mounting base.
- Non-sparking ratchet assembly.
- Declutching arbor to prevent damage from reverse winding.
- Standard inlet: 90° stainless steel ball bearing swivel joint, 1/2" female NPT threads.
- Standard outlet: 1/2" female NPT threads.
- Standard pressures to 3000 psi (207 bar).
- Temperatures from +20°F to +400°F (-7°C to +204°C).
- Consult factory for other pressures and temperatures.
- 4-way roller assembly.
- Constant tension is available – consult factory.
- 304 stainless steel construction.
- Optional SST Mosmatic 1/2" balanced pressure swivel joint available, subtract 1.50" from "F" dimension, specify when ordering.

Used For

- Lubrication
- Potable water
- Chemical transfer
- Washdown
- Corrosive environments



PARTS DRAWING – ISO 171

Model Number	Hose Capacity of Reel feet m				Approx. Weight lb. kg			Std. Roller Assy.	Reel Dimensions*** in. mm							
	I.D. in. mm	1/4 6	3/8 10	1/2 13	NET	UPS/ FedEx SHIP WT.	Freight SHIP WT.		A	B	C	E	F	G	H	X
	O.D. in. mm	5/8 16	3/4 19	7/8 22												
SSN716-16-17-10.5J	–	35	35	66	75*	108	N204S	10	4	10.5	18.5	13	17	9.12	8	
	–	11	11	30	34	49		254	102	267	470	330	432	232	203	
SSN716-19-20-10.5J	–	50	50	67	82*	109	N204S	10	4	10.5	20.75	13	20	10.62	8	
	–	15	15	30	37	49		254	102	267	527	330	508	270	203	
SSN716-23-24-15.5J	–	65	65	79	92*	114	N204S	10	4	15.5	23.75	13	24	12.62	8	
	–	20	20	36	42	52		254	102	394	603	330	610	321	203	
SSN716-23-24-15.5G	100	75	65	94	101*	129	N204S	10	4	15.5	23.75	13	24	12.62	8	
	30	23	20	43	46	59		254	102	394	603	330	610	321	203	
SSN716-25-26-15.5B	–	75	75	90	–	125	N204S	10	4	15.5	25.25	13	26	13.62	8	
	–	23	23	41	–	57		254	102	394	641	330	660	346	203	
SSN718-25-26-15.5G	–	100	100	96	–	131	N206S	12	6	15.5	25.25	15	26	13.62	10	
	–	30	30	44	–	59		305	152	394	641	381	660	346	254	

Notes:

1. Specifications subject to change.
 2. Reel models and capacities shown are for standard drag applications; for vertical lift applications, consult factory.
 3. Other sizes, from standard components, available on request.
 4. Finish: Refer to page 2.
 5. Be sure to check dimensions and weights prior to ordering.
- NOTICE:** A flexible connector must be used between the inlet pipe and the inlet swivel joint.
- * Dimensional weight applies when shipped as a parcel package (via FedEx or UPS Ground).
- ***X, Y indicate mounting holes. See page 2.

Available Roller Positions



SR (STD)



VR (OPT)



TR (OPT)



TR (Wallmount)

