

Compact Manual Rewind Reels

Hannay Series SS1500

To handle single 3/8" through 5/8" I.D. hose

Features

- Lightweight, compact reels designed for long lengths of hose.
- Direct crank rewind is permanently attached.
- Cam-lock drag brake, spring actuated pin lock.
- Standard inlet: 90° stainless steel ball bearing swivel joint, 1/2" female NPT threads.
- Standard outlet: 1/2" female NPT threads.
- Rollers and roller mounting brackets are accessory items. Specify roller position.
- Pressures to 3000 psi (207 bar).
- Temperatures from +20°F to +400°F (-7°C to +204°C).
- Consult factory for other pressures and temperatures.
- Consult factory for power version.
- 304 stainless steel construction.

Used For

- Pest control
- Pressure washing
- Steam cleaning



PARTS DRAWING – ISO 175

| Model Number | Hose Capacity of Reel feet m | | | | Approx. Weight Crank Rewind lb. kg | | | Reel Dimensions*** in. mm | | | | |
|--------------|---------------------------------|-----------|-----------|-----------|--|------------------------------|------------------------|------------------------------|-----|------|-------|------|
| | I.D. in. mm | 3/8 10 | 1/2 13 | 5/8 16 | NET | UPS/ FedEx SHIP Wt. | Freight SHIP Wt. | A | B | E | F | X |
| | O.D. in. mm | 3/4 19 | 7/8 22 | 1 25 | | | | | | | | |
| SS1514-17-18 | | 125 | 75 | 50 | 27 | 65* | 62 | 11 | 6 | 16.5 | 19.25 | 9.5 |
| | | 38 | 23 | 15 | 12 | 30 | 28 | 279 | 152 | 419 | 489 | 241 |
| SS1520-17-18 | | 275 | 175 | 125 | 29 | 80* | 64 | 17 | 12 | 16.5 | 25.25 | 15.5 |
| | | 84 | 53 | 38 | 13 | 36 | 29 | 432 | 305 | 419 | 641 | 394 |
| SS1526-17-18 | | 400 | 300 | 200 | 31 | 98* | 66 | 23 | 18 | 16.5 | 31.25 | 21.5 |
| | | 122 | 91 | 61 | 14 | 45 | 30 | 584 | 457 | 419 | 794 | 546 |
| SS1530-17-18 | | 500 | 375 | 275 | 33 | 110* | 68 | 27 | 22 | 16.5 | 35.25 | 25.5 |
| | | 152 | 114 | 84 | 15 | 50 | 31 | 686 | 559 | 419 | 895 | 648 |
| SS1536-17-18 | | – | 475 | 350 | 35 | 129* | 70 | 33 | 28 | 16.5 | 41.25 | 31.5 |
| | | – | 145 | 107 | 16 | 59 | 32 | 838 | 711 | 419 | 1048 | 800 |

Notes:

1. Specifications subject to change.
 2. Upon request, reels can be supplied with drum lengths other than shown.
 3. Dimension "F" is the overall length of standard model reels.
 4. Manual rewind available in RT or LB configurations only.
 5. Finish: Refer to page 2.
 6. Be sure to check dimensions and weights prior to ordering.
- NOTICE:** A flexible connector must be used between the inlet pipe and the inlet swivel joint.
- * Dimensional weight applies when shipped as a parcel package (via FedEx or UPS Ground).
- ***X, Y indicate mounting holes. See page 2.

