

Manual Rewind Reels

Hannay Series SS4000

To handle 3/4" or 1" I.D. hose

Features

- Lightweight, compact reels designed for long lengths of hose.
- Direct crank rewind is removable.
- Cam-lock brake, spring-actuated pin lock.
- Standard inlet: 90° stainless steel ball bearing swivel joint, 1" female NPT threads.
- Standard outlet: 1" female NPT threads.
- Rollers and roller mounting brackets are accessory items. Specify roller position.
- Pressures to 1000 psi (69 bar).
- Temperatures from +20°F to +400°F (-7°C to +204°C).
- Consult factory for other pressures and temperatures.
- 304 stainless steel construction.

Used For

- Food processing
- Bottling plants
- Fire protection
- Water supply
- Chemical transfer



PARTS DRAWING – ISO 178

Model Number	Hose Capacity of Reel feet m			Approx. Weight Crank Rewind lb. kg			Reel Dimensions*** in. mm				
	I.D. in. mm	3/4 19	1 25	NET	UPS/ FedEx SHIP Wt.	Freight SHIP Wt.	A	B	E	F	X
	O.D. in. mm	1-9/32 33	1-1/2 40								
SS4018-17-18	50	35	36	80*	71	15	10	16.5	27.75	13.5	
	15	11	16	36	32	254	419	686	705	102	
SS4024-17-18	100	50	46	98*	81	21	16	16.5	33.75	19.5	
	30	15	21	45	37	533	406	419	857	495	
SS4030-17-18	150	75	57	110*	92	27	22	16.5	39.75	25.5	
	46	23	26	50	42	686	559	419	1010	648	
SS4038-17-18	200	100	70	-	124	35	30	16.5	47.75	33.5	
	61	30	32	-	56	889	762	419	1213	851	

Notes:

1. Specifications subject to change.
2. Upon request, reels can be supplied with drum lengths other than shown.
3. Dimension "F" is the overall length of standard model reels. Crank rewind reels require 3-1/2" clearance to remove or install crank handle.
4. Finish: Refer to page 2.

5. Be sure to check dimensions and weights prior to ordering.

NOTICE: A flexible connector must be used between the inlet pipe and the inlet swivel joint.

* Dimensional weight applies when shipped as a parcel package (via FedEx or UPS Ground).

***X, Y indicate mounting holes. See page 2.

