

Spring Rewind Reels

Hannay Series SS800

To handle 3/4" or 1" I.D. hose

Features

- Square tubing frame for heavy-duty applications.
- Non-sparking ratchet assembly.
- Declutching arbor to prevent damage from reverse winding.
- Standard inlet: 90° stainless steel ball bearing swivel joint, 1" female NPT threads.
- Standard outlet: 1" female NPT threads.
- Pressures to 1000 psi (69 bar).
- Temperatures from +20°F to +400°F (-7°C to +204°C).
- Consult factory for other pressures and temperatures.
- 4-way roller assembly.
- Constant tension is available – consult factory.
- 304 stainless steel construction.

Used For

- Dairy
- Caustic materials
- Air / water
- Chemical / food transfer



PARTS DRAWING – ISO 198

Model Number	Hose Capacity of Reel feet m			Approx. Weight lb. kg		Std. Roller Assy.	Reel Dimensions*** in. mm									
	I.D. in. mm	3/4 19	1 25	NET	SHIP		A	B	C	D	E	F	G	H	X	Y
	O.D. in. mm	1-9/32 33	1-1/2 40													
SS816-25-26-10.5B	60	35	96	131	R204S	9.25	4	10.5	25	26.12	14.75	25.88	13.5	4.5	21.75	
	18	11	44	59		235	102	267	635	663	375	657	343	114	552	
SS818-25-26-10.5B	70	50	102	137	R206S	11.25	6	10.5	25	26.12	16.75	25.88	13.5	6.5	21.75	
	21	15	46	62		286	152	267	635	663	425	657	343	165	552	
SS820-25-26-10.5A	85	75	131	166	R308S	13.25	8	10.5	25	27	19.5	25.88	13.5	8.5	21.75	
	26	23	59	75		337	203	267	635	686	495	657	343	216	552	
SS820-30-31-10.5A	-	100	137	172	R308S	13.25	8	10.5	28.5	30.5	19.5	31.38	17	8.5	25.25	
	-	30	62	78		337	203	267	724	775	495	797	432	216	641	
SS820-30-31-15.5A	100	-	145	180	R308S	13.25	8	15.5	28.5	30.5	19.5	31.38	17	8.5	25.25	
	30	-	66	82		337	203	394	724	775	495	797	432	216	641	

Notes:

1. Specifications subject to change.
2. Reel models and capacities shown are for standard drag applications; for vertical lift applications, consult factory.
3. Other sizes, from standard components, available on request.
4. Finish: Refer to page 2.
5. **Be sure to check dimensions and weights prior to ordering.**

NOTICE: A flexible connector must be used between the inlet pipe and the inlet swivel joint.

***X, Y indicate mounting holes. See page 2.

Available Roller Positions

SR (STD)VR (OPT)TR (OPT)TR (Wallmount)