

Order no: **9005W**



SILVENT 9005W: an energy-efficient flat nozzle that generates a strong, efficient blowing force at an exceptionally low noise level.

Compressed air is optimally used in this flat nozzle, which through its unique design introduces a completely new blowing technology feature.

The aerodynamic nozzle design achieves the effect by maximising entrainment of air.

Each orifice is also uniquely designed to optimise the entrainment area.

The air nozzle – SILVENT 9005W – is made exclusively of Zytel, a high-performance material without which the unique and truly complex Laval orifices would not be possible.

These small orifices combined with the aerodynamic slots of the nozzle provide high efficiency.

The nozzle is ideal for blowing applications that require extra blowing force and an extra wide air cone.

TECHNICAL DATA

Replace open pipe Ø (mm)	10
Blowing force (N)	15.0
Air consumption (Nm³/h)	76
Sound level (dB(A))	87
Nozzle technology	Laval
Material (nozzle)	ZYTEL
Connection	G 1/4"
Weight (kg)	0.0350
Max temp (°C)	180
Max op. pressure (MPa)	1.0

Noise reduction* **82%**

Energy savings* **59%**

Material specification: Zytel HTN FG52G35 HSL BK011, Desmopan 487, EN 10088-3

Blowing dist. (mm)	Blowing coverage (mm)
50	100
100	120
200	160
300	200
400	240
500	280

*For further information, see page 150 or visit silvent.com.

Dimensions

