Strahman Hose Assemblies


Strahman has been supplying industrial strength hoses since 1921. We combine years of solid craftsmanship and innovative new solutions to offer hoses that are safe, reliable, durable, and easy to maintain.

All Strahman hoses are assembled with bronze, bronze chrome-plated, or stainless steel fittings. Some hoses include stainless steel internal spring assemblies on one or both ends for added durability and extended hose life.

Shown (top to bottom):

- %"I.D. / 11/8" O.D. Extruded yellow hose with FDA approved internal tube.
 Also available in black and white.
- %"I.D. / 1½" O.D. Premium Wrapped black hose with FDA internal tube.
- %"I.D. / 1½" O.D. Premium Wrapped white hose with FDA internal tube — food grade hose.
- %"I.D. / 1½" O.D. Premium Wrapped red hose with FDA approved internal tube.

NOTE: Strahman hoses come standard in 25, 50, 75, and 100 foot lengths. Standard length 50 foot hose supplied for use on mixing unitshose stations. Check with factory if longer length is required.



STRAHMAN HOSE ASSEMBLIES					
HOSE I.D. /O.D. DESCRIPTION	COLORS AVAILABLE	TEMPERATURE RATING	MAXIMUM WORKING PRESSURE	MINIMUM BURST	USE/RATING CODE
5/8" I.D. / 11/8" O.D. EXTRUD-	BLACK, YELLOW, WHITE	-20 to 200°F	300 psi	1,500	A
5/8" I.D. / 11/8" O.D. PREMIUM WRAPPED	RED, WHITE, BLACK	-20 to 200°F	300 psi	1,500	В

Note: When used with mixing-unit hose stations, the maximum pressure rating will be 150 psi.

Note: Do not excessively tighten hose end nut during installation.

USE/RATING CODES:

A: USE - Excellent abrasion resistance, oil, fat and chemical resistance.

B: USE - Oil, fat and chemical resistance.

RATING - General purpose hose for food, water and air with FDA approved tube.

RATING - General purpose hose for food, water and air with FDA approved tube.



Mobile: 0800 NOZZLE Email: sales@spraynozzle.co.nz