

Medium - High Flow Low Pressure

Lances & Gun Accessories

Economy Range

Photo	Order Part Number	Material	Description
	TM-HBBB-220-LAN	Stainless steel	1/2" lance mounting gun, length 22cm
	TM-HSVB-100	Stainless steel	Guarded ball valve in stainless steel(316); 1/2" female x quick release coupler with rubber protection. Max. pressure: 20 Bar Max. temperature: 93° C
	TM-HSVB-200	Stainless steel	Shielded in stainless steel(304); 1/2" female x quick release coupler with rubber protection. Max. pressure: 20 Bar Max. temperature: 93° C
	TM-HSVB-300	Stainless steel	Shielded in stainless steel(304); Inlet and Outlet Connections: 1/2" female Max. pressure: 20 Bar Max. temperature: 93° C
	TM-SNQC-220-LAN	Stainless steel	Quick coupler lance x 1/2", length 22cm
	TM-SNQC-500-LAN	Stainless steel	Quick coupler lance x 1/2", length 50cm
	TM-SNQC-500-LAN-FN	Stainless steel	Stainless lance with protected foam nozzle, length 50cm
	TM-SFQC	Stainless steel	Quick coupler stainless adaptor with foam nozzle
	TM-SNF-220-LAN	Stainless steel	Threaded lance stainless (316) x 1/2" female, length 22cm
	TM-SNF-500-LAN	Stainless steel	Threaded lance stainless (316) x 1/2" female, length 50cm

Always consult factory for product suitability & technical data